

Eco78-LED



Product Description

Economically Priced, Flat, Recessed LED Spotlight

Eco78-LED is a economically priced flat, recessed, spotlight LED with a frosted lens that helps reduce glare and provides a smooth, even illumination. Eco78-LED can be surface mounted or recessed and is perfect for displays, cabinets, and furniture.

Product Features

- Available color temperatures:
 - 3000 K
 - 4000 K
 - Additional color temperatures (special order)
- Attached 79" connecting cable with a plug-in connector
- Surface mount ring included
- Dimmable with available accessories
- White or Stainless Steel
- To be used with 24 Vdc Constant Voltage Driver
- 30,000 hours of usable life
- Efficacy: 70 lm/W
- Energy-efficient: uses only 3 W
- Good CRI >80
- Recess depth: 5/16"






Available Options

Necessary Accessories on Page 68

MODEL	DIAMETER	POWER	LIGHT OUTPUT	EFFICACY	CRI	FINISH	PART NO. (3000 K)	PART NO. (4000 K)
Eco78-LED	3 3/8"	3 W	210 Lm	70 lm/W	>80	White	ECO78/WH/3000	ECO78/WH/4000
Eco78-LED	3 3/8"	3 W	210 Lm	70 lm/W	>80	Stainless Steel	ECO78/SS/3000	ECO78/SS/4000

Compatible Drivers on Page 64

Dimensions



Spot-LED Accessories

Eco78-LED

Connecting Cables

DESCRIPTION	LENGTH	PART NO.
Power Cable Extension, White	39"	KB12LEDCC39/H
Power Cable Extension, White	84"	KB12LEDCC84/H
Power Cable Extension, White	98"	KB12LEDCC98/H
Power Cable Extension, Black	39"	KB12LEDCC39/BL/H
Power Cable Extension, Black	39"	KB12LEDCC98/BL/H
Power Cable Extension, Black	39"	KB12LEDCC120/BL/H
Terminal Block	39"	PS24V/TB
Terminal Block, DC plug	39"	PS24V/TB/DC/Y
Power Cord locking clip		CLIP/24V/CCPC

Optional Accessories

DESCRIPTION	PART NO.
Dimming Module	PS24V/DIM/EURO
Dimming Controller	DIMCONTROL/EURO
Y-Cable Adapter	STICKDIM/YCABLE
Remote Control Dimmer	RCPSDIM/V2
Rocker Switch	PS24V/SWITCH/RS/H
Rocker Switch, DC plug	PS24V/SWITCH/RS/DC1224/H
24 V Occupancy Switch	PS24V/SW/OC
Sensor Switch	IRSWITCH/H
Sensor Switch, Dimmable	IRSWITCH/H/D
Surface Mount Ring, Stainless Steel	DIR68/SS
Surface Mount Ring, Matte Chrome	DIR68/MC

Non Swivel

R55-LED

Connecting Cables

DESCRIPTION	LENGTH	PART NO.
Power Cable Extension, White	39"	KB12LEDCC39/H
Power Cable Extension, White	84"	KB12LEDCC84/H
Power Cable Extension, White	98"	KB12LEDCC98/H
Power Cable Extension, Black	39"	KB12LEDCC39/BL/H
Power Cable Extension, Black	39"	KB12LEDCC98/BL/H
Power Cable Extension, Black	39"	KB12LEDCC120/BL/H
Terminal Block	39"	PS24V/TB
Terminal Block, DC plug	39"	PS24V/TB/DC/Y
Power Cord locking clip		CLIP/24V/CCPC

Optional Accessories

DESCRIPTION	PART NO.
Dimming Module	PS24V/DIM/EURO
Dimming Controller	DIMCONTROL/EURO
Y-Cable Adapter	STICKDIM/YCABLE
Remote Control Dimmer	RCPSDIM/V2
Rocker Switch	PS24V/SWITCH/RS/H
Rocker Switch, DC plug	PS24V/SWITCH/RS/DC1224/H
24 V Occupancy Switch	PS24V/SW/OC
Sensor Switch	IRSWITCH/H
Sensor Switch, Dimmable	IRSWITCH/H/D
Surface Mount Ring, Matte Chrome	DIR55/MC
Surface Mount Ring, Stainless Steel	DIR55/SS
Surface Mount Ring, White	DIR55/WH

Low Voltage Drivers

Constant Voltage Drivers

24 Vdc Drivers



Daisy Driver, 30W
(Full Specs on Page #114)



Daisy Driver, 75W
(Full Specs on Page #115)



Daisy Driver, 96W
(Full Specs on Page #116)



Driver, 6W
(Full Specs on Page #117)

Constant Current Drivers

LED Drivers



LED Driver, 10W
(Full Specs on Page #118)



LED Driver, 18W Dimmable
(Full Specs on Page #119)

Compatibility

Constant Voltage Compatible LEDs

SPOT

SR45-LED

FR68-LED

Eco78-LED

R55-LED

ER-LED

SR68-LED CV

Constant Current Compatible LEDs

SPOT

SR68-LED

HO-LED2

Eye-LED