roduct Details

SR68-LED



Product Description -

Recessed Swivel LED Spotlight with Extremely High Light Output

SR68-LED is a fully directional, high output, swivel LED spotlight. It is recessed and designed for applications where drawing attention to a specific area or object is important

Product Features —



- 3000 K
- 4000 K
- Additional color temperatures (special order)
- Attached 98" connecting cable with a plug-in connector
- 20° swivel and tilt to either side
- Approved for use in closet applications

- Dimmable with available accessories
- High quality Brushed Aluminum housing
- Recess depth 1 1/2"
- 70,000 hours usable life
- Excellent CRI >90
- Efficacy: 104 lm/W
- Energy-efficient: uses 5 W












Available Options

Necessary Accessories on Page 74

| MODEL | DIAMETER | POWER | LIGHT OUTPUT | EFFICACY | CRI | FINISH | PART NO. (3000 K) | PART NO. (4000 K) | |
|----------|----------|-------|-----------------|----------|-----|------------------|----------------------|----------------------|--|
| SR68-LED | 3 5/32" | 5 W | 525 Lm | 104 lm/W | >90 | Brushed Aluminum | SR68/SS/3000/90 | SR68/CW | |

Compatible Drivers on Page 72



55 www.heralighting.com

Low Voltage Drivers

Constant Voltage Drivers

24 Vdc Drivers



Daisy Driver, 30W (Full Specs on Page #94)



Daisy Driver, 75W (Full Specs on Page #95)



Daisy Driver, 96W (Full Specs on Page #96)



Driver, 6W (Full Specs on Page #98)

Constant Current Drivers

LED Drivers



LED Driver, 10W (Full Specs on Page #104)



LED Driver, 18W Dimmable (Full Specs on Page #105)

Compatibility

Constant Voltage Compatible LEDs

SPOT

SR45-LED

FR68-LED

Eco78-LED

R55-LED

ER-LED

Constant Current Compatible LEDs

SPOT

SR45-LED

SR68-LED

Big6/2-LED

HO-LED

Eye-LED

www.heralighting.com

Spot-LED Accessories

SR45-LED

Connecting Cables

| DESCRIPTION | LENGTH | PART NO. |
|---------------------------------------|--------|-------------------|
| 350mA Power Cable Extension, Black | 36" | LEDCC36 |
| 350mA Power Cable Extension, Black | 72" | LEDCC72 |
| 350mA Terminal Block, 3 way | 98" | TBLED/B |
| 24V Power Cable Extension, White | 39" | KB12LEDCC39/H |
| 24V Power Cable Extension, White | 84" | KB12LEDCC84/H |
| 24V Power Cable Extension, White | 98" | KB12LEDCC98/H |
| 24V Power Cable Extension, Black | 39" | KB12LEDCC39/BL/H |
| 24V Power Cable Extension, Black | 39" | KB12LEDCC98/BL/H |
| 24V Power Cable Extension, Black | 39" | KB12LEDCC120/BL/H |
| 24V Terminal Block | | PS24V/TB |
| 24V Terminal Block, DC plug | | PS24V/TB/DC/Y |
| 24V Power Cord locking clip | | CLIP/24V/CCPC |

Optional Accessories

| DESCRIPTION | PART NO. |
|-----------------------------|--------------------------|
| Dimming Controller | DIMCONTROL/EURO |
| Y-Cable adapter | STICKDIM/YCABLE |
| 24V Dimming Module | STICKPSDIM/S |
| 24V Remote Control Dimmer | RCPSDIM/V2 |
| 24V Rocker Switch | PS24V/SWITCH/RS/H |
| 24V Rocker Switch, DC plug | PS24V/SWITCH/RS/DC1224/H |
| 24V Occupancy Switch | PS24V/SW/OC |
| 24V Sensor Switch | IRSWITCH/H |
| 24V Sensor Switch, Dimmable | IRSWITCH/H/D |

SR68-LED

Connecting Cables

| FINISH | LENGTH | PART NO. |
|---------------------------------------|--------|----------|
| 350mA Power Cable Extension, Black | 36" | LEDCC36 |
| 350mA Power Cable Extension, Black | 72" | LEDCC72 |
| 350mA Terminal Block, 3 way | 98" | TBLED/B |

Optional Accessories

| DESCRIPTION | PART NO. | |
|--------------------|-----------------|--|
| Dimming Controller | DIMCONTROL/EURO | |
| Y-Cable Adapter | STICKDIM/YCABLE | |

74 www.heralighting.com